



Approved for use in the Wildland Urban Interface (W.U.I.)

Chapter 7A compliant: Tested and listed to ASTM2886.
OSFM BML listing: 8165-2426 | QAI listing: B1155




Revision Date: February 25, 2020




V2VENTS.COM (916) 652-7424 info@firestormbuildingproducts.com P.O. Box 1126 Loomis, CA. 95650




For use to comply with IWUI, IBHS Wildfire Prepared Certification, California Chapter 7A*




TOP VIEW




Intumescent Core



BOTTOM VIEW



ISOMETRIC VIEW



SIDE VIEW

Required Installation:


Use EverKem 814+ intumescent firestop caulking or equivalent, **BEHIND** flanges.
For application details and installation examples, please visit www.V2Vents.com

FSVER2M PRODUCT SPECIFICATION & DATA SHEET

Proudly Manufactured By:



www.newcalmetals.com



Model Description	Round Eave Vent	Flange Type	NFVA	Flange Front	2 sq. in.	Frame & Flange	Intumescent Core	G90 Galvanized Steel - 26GA
Model Number	FSVER2M							5mm Hexagonal Matrix - Aluminum with intumescent coating
Model Size	2" x 2"							14 Mesh - 304 Stainless Steel
								Stainless Steel Screen - 1/8" (Faces exterior)