



Approved for use in the Wildland Urban Interface (W.U.I.)

Chapter 7A compliant: Tested and listed to ASTM2886.
OSFM BML listing: 8165-2426 | QAI listing: B1155


Revision Date: February 24, 2026




V2VENTS.COM (916) 652-7424 info@firestormbuildingproducts.com P.O. Box 1126 Loomis, CA. 95650




For use to comply with IWUI, IBHS Wildfire Prepared Certification, California Chapter 7A*




TOP VIEW




END VIEW



Intumescent Core



ISOMETRIC VIEWS



Reuired Installation:

Use EverKem 814+ intumescent firestop caulking or equivalent, **BEHIND** flanges.
For application details and installation examples, please visit www.V2Vents.com

FSVSC5120 SS PRODUCT SPECIFICATION & DATA SHEET

Model Description	Continuous Vent	Flange Type	Standard
Model Number	FSVSC5120 SS	NFVA	240 sq. in.
Model Size	5" x 120"		

Frame & Flange	G90 Stainless Steel (1/8" holes) - 24GA
Intumescent Core	5mm Hexagonal Matrix - Aluminum with intumescent coating
Ember Mesh	14 Mesh - 304 Stainless Steel
Pest Screen	Stainless Steel Screen - 1/8" (Faces exterior)

Proudly Manufactured By:



www.newcalmetals.com

